



Reference design for secure industrial IoT devices based on STM32MP13x

- ▶ Single Board Computer based on the solderable DHCOR STM32MP13
- ▶ Compatible with accessories from the Raspberry Pi® community
- ▶ Highlights: Bluetooth / WiFi, Dual GB Ethernet, Secure Boot, OP-TEE support
- ▶ Trusted Platform Module 2.0 available on request
- ▶ Mainline Linux support and active software maintenance
- ▶ Industrial product design
- ▶ Guaranteed long-term availability of 10+ years

Technical Data

Board type	Single Board Computer
CPU details	STM32MP135F 1x ARM® Cortex-A7 up to 1 GHz
CPU vendor	STM
CPU type	Cortex-A7
Co-processor available	✗

Number of cores	1
GPU available	✗
PMIC	STPMIC1D
Security	Crypto Engine, Secure Boot 3072-bit fuses including 96-bit unique ID, up to 1280 bits available for user and 256-bit HUK to protect AES 256 keys Hardware acceleration: AES 128, 192, 256 DES/TDES AES 128, 256 with DPA protection PKA ECC/RSA with DPA protection AES 128 on-the-fly DRAM encryption and decryption HASH (SHA-1, SHA-224, SHA-256, SHA-384, SHA-512, SHA-3), HMAC 1 x true random number generator (6 triple oscillators) 1 x CRC calculation unit
DDR3L DRAM	512 MB
eMMC flash	4 GB
SPI NOR flash	4 MB
EEPROM	4 kB
Additional RTC	Temp. compensated RTC RV-3032-C7
Bluetooth available	✓
Bluetooth version	Bluetooth® v5.2
WiFi available	✓
WiFi version	Single band 802.11b/g/n
Ethernet	2x 1 Gbit/s
USB	USB host: 1x USB 2.0 high-speed USB device: 1x USB 2.0 Type-C high-speed
UART (serial console)	1x TTL
TPM (Trusted Platform Module)	TPM 2.0 device ST33TPHF2XSPI

Battery socket	CR1216, CR1220, CR1225
Buttons	1x power, 1x reset
Boot mode	3 bit boot mode switch
Debug interface	JTAG
BSP	Linux Yocto (Debian on request)
Power supply	5 VDC, USB Type-C power supply port
Operating temperature	-25 to 70 °C
Storage temperature	-25 to 70 °C
Dimensions	85 x 56 x 18 mm

Raspberry Pi 40-pin Expansion

I2C	1x
UART	2x
SPI	1x
I2S/SAI	1x
PWM	2x
CAN	2x
GPIO	up to 28x

Configurations

Item Number	Model (other configurations on request)	Product description
-------------	-----------------------------------------	---------------------

HS00035

DHSBC STM32MP13

STM32MP135F qwith 1GHz, Crypto, 512MByte DDR3L memory, 4kb
EEPROM, 4GB eMMC, SPI flash, WiFi/BT, RTC Ta -25 to +70°C

* Other configurations on request